





Description

BWS, track spotlight, CoB LED, 27W, warm white 3000K, 700mA, with 3-phase adapter, including power supply, rotatable, 60° reflector, clear protective glass, housing body white and heat sink black, for ONETRACK

General data

Adjustability:	Rotating and swivelling
Colour housing:	Black
Degree of protection (IP):	IP20
Lamp holder:	None
Material housing:	Aluminium
Protection class:	I
Suitable for light-track mounting:	Yes
Surface protection:	Powder coating

Photometric data

Beam angle:	Wide beam 41-80°
Colour consistency (McAdam ellipse):	SDCM3
Colour of light:	White
Colour rendering index CRI:	90-100
Colour temperature:	3500K
Light outlet:	Direct
Light sharing:	Symmetric
Luminaire efficacy:	125lm/W
Luminous flux:	3377lm
Max. system power:	27W
Rated luminous flux according to IEC 62722-2-1:	3377lm
Suitable for number of lamps:	1

Electrical data

Connection type: Busbar adapter







Dimming DALI:	Yes
Exchangeable control gear:	Yes
Nominal current:	700mA
Nominal voltage:	220V - 240V
Voltage type:	AC
With control gear:	Yes

Product dimensions

Height/depth:	188mm
Length:	130mm
Outer diameter:	79mm
Width:	79mm



Adress/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de