





## Description

BWS, track spotlight, CoB LED, 27W, warm white 3000K, 700mA, with 3-phase adapter, including power supply, rotatable, 24° reflector, clear protective glass, housing body white and heat sink black, for ONETRACK

## General data

|                                           |                         |
|-------------------------------------------|-------------------------|
| <b>Adjustability:</b>                     | Rotating and swivelling |
| <b>Colour housing:</b>                    | Black                   |
| <b>Degree of protection (IP):</b>         | IP20                    |
| <b>Lamp holder:</b>                       | None                    |
| <b>Material housing:</b>                  | Aluminium               |
| <b>Protection class:</b>                  | I                       |
| <b>Suitable for light-track mounting:</b> | Yes                     |
| <b>Surface protection:</b>                | Powder coating          |

## Photometric data

|                                                        |                    |
|--------------------------------------------------------|--------------------|
| <b>Beam angle:</b>                                     | Medium beam 21-40° |
| <b>Colour consistency (McAdam ellipse):</b>            | SDCM3              |
| <b>Colour of light:</b>                                | White              |
| <b>Colour rendering index CRI:</b>                     | 90-100             |
| <b>Colour temperature:</b>                             | 3500K              |
| <b>Light outlet:</b>                                   | Direct             |
| <b>Light sharing:</b>                                  | Symmetric          |
| <b>Luminaire efficacy:</b>                             | 126lm/W            |
| <b>Luminous flux:</b>                                  | 3415lm             |
| <b>Max. system power:</b>                              | 27W                |
| <b>Rated luminous flux according to IEC 62722-2-1:</b> | 3415lm             |
| <b>Suitable for number of lamps:</b>                   | 1                  |

## Electrical data

**Connection type:** Busbar adapter







|                                   |             |
|-----------------------------------|-------------|
| <b>Dimming DALI:</b>              | Yes         |
| <b>Exchangeable control gear:</b> | Yes         |
| <b>Nominal current:</b>           | 700mA       |
| <b>Nominal voltage:</b>           | 220V - 240V |
| <b>Voltage type:</b>              | AC          |
| <b>With control gear:</b>         | Yes         |

#### Product dimensions

|                        |       |
|------------------------|-------|
| <b>Height/depth:</b>   | 188mm |
| <b>Length:</b>         | 130mm |
| <b>Outer diameter:</b> | 79mm  |
| <b>Width:</b>          | 79mm  |



#### Adress/Contact

A.L.S. Architektonische Lichtsysteme GmbH  
Mastorter Str. 31 | 88069 Tettnang (Germany)  
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30  
E-Mail: [info@als.de](mailto:info@als.de) | Web: [www.als.de](http://www.als.de)