




Description

BWS, Spotlight for contact track, CoB LED, 40W, 2700K, 1050mA, CRI >80, mit 3-phasen-adapter, incl. power supply, 40° beam angel, clear tempered glass, body black

General data

Adjustability:	Rotating and swivelling
Colour housing:	Black
Degree of protection (IP):	IP20
Lamp holder:	None
Material housing:	Aluminium
Protection class:	I
Suitable for light-track mounting:	Yes
Surface protection:	Powder coating

Photometric data

Beam angle:	Medium beam 21-40°
Colour consistency (McAdam ellipse):	SDCM3
Colour of light:	White
Colour rendering index CRI:	90-100
Colour temperature:	2700K
Light outlet:	Direct
Light sharing:	Symmetric
Luminaire efficacy:	132lm/W
Luminous flux:	5137lm
Max. system power:	39W
Rated luminous flux according to IEC 62722-2-1:	5137lm
Suitable for number of lamps:	1

Electrical data

Nominal voltage:	220V - 240V
Voltage type:	AC



Address/Contact



A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de



With control gear:	Yes
Connection type:	Busbar adapter
Exchangeable control gear:	Yes
No dim function:	Yes
Nominal current:	700mA

Product dimensions

Height/depth:	196mm
Length:	150mm
Outer diameter:	99mm
Width:	99mm



Adress/Contact