

BWS 30



- LED Schienenstrahler
- Gehäuse aus lackiertem Alu-Druckguss, klares Schutzglas
- COB-LED-Modul in 4 Ausstrahlwinkeln 15°/24°/40°/60°
- Eutrac®-3-Phasen-Adapter
- 4 Standard Gehäusefarbkombinationen (andere Farbkombinationen auf Anfrage)
- Schutzart: IP20
- Schutzklasse: I
- Integriertes elektronisches Versorgungsteil (Standard: 30.000h / 50.000h auf Anfrage)
- CRI >90

Auf Anfrage

- Dimmbare Version
- Anbaumontage mit Deckenrosette
- Einhängestrahler für Rasterdecken
- Für Lebensmittel (Gemüse-, Back- und Fleischwaren) optimierte Versionen

- LED power-track-light
- Body in coated die-cast aluminium, clear glass
- COB-LED-module with optics in 15°/24°/40°/60°
- Eutrac®-3-phase-adapter
- 4 standard housing colours combination (other colour combinations on request)
- Protection Rating: IP20
- Protection Class: I
- Built in electronic power supply (standard 30.000h / 50.000h on request)
- CRI >90

On request

- Dimmable version
- Surface mounted with ceiling rose
- Spotlight to hang in grid ceilings
- Optimized versions for groceries (vegetables, bakery and meat products)

Stromschienen | Power-tracks

Siehe ab Seite 50 | See from page 50





Ab/From
01/2024
120lm/W



BWS-30 | 220-240 V | LED | CRI 90




15°					27 W
4000 K	BWS-30NW11-1S	BWS-30NW12S	BWS-30NW12-1S	BWS-30NW17-7S	3430 lm
3500 K	BWS-30WNW11-1S	BWS-30WNW12S	BWS-30WNW12-1S	BWS-30WNW17-7S	3242 lm
3000 K	BWS-30WW11-1S	BWS-30WW12S	BWS-30WW12-1S	BWS-30WW17-7S	3210 lm
2700 K	BWS-30SW11-1S	BWS-30SW12S	BWS-30SW12-1S	BWS-30SW17-7S	3146 lm
24°					27 W
4000 K	BWS-30NW11-1	BWS-30NW12	BWS-30NW12-1	BWS-30NW17-7	3449 lm
3500 K	BWS-30WNW11-1	BWS-30WNW12	BWS-30WNW12-1	BWS-30WNW17-7	3415 lm
3000 K	BWS-30WW11-1	BWS-30WW12	BWS-30WW12-1	BWS-30WW17-7	3381 lm
2700 K	BWS-30SW11-1	BWS-30SW12	BWS-30SW12-1	BWS-30SW17-7	3314 lm
40°					27 W
4000 K	BWS-30NW11-1F	BWS-30NW12F	BWS-30NW12-1F	BWS-30NW17-7F	3491 lm
3500 K	BWS-30WNW11-1F	BWS-30WNW12F	BWS-30WNW12-1F	BWS-30WNW17-7F	3456 lm
3000 K	BWS-30WW11-1F	BWS-30WW12F	BWS-30WW12-1F	BWS-30WW17-7F	3422 lm
2700 K	BWS-30SW11-1F	BWS-30SW12F	BWS-30SW12-1F	BWS-30SW17-7F	3354 lm
60°					27 W
4000 K	BWS-30NW11-1-60	BWS-30NW12-60	BWS-30NW12-1-60	BWS-30NW17-7-60	3491 lm
3500 K	BWS-30WNW11-1-60	BWS-30WNW12-60	BWS-30WNW12-1-60	BWS-30WNW17-7-60	3377 lm
3000 K	BWS-30WW11-1-60	BWS-30WW12-60	BWS-30WW12-1-60	BWS-30WW17-7-60	3344 lm
2700 K	BWS-30SW11-1-60	BWS-30SW12-60	BWS-30SW12-1-60	BWS-30SW17-7-60	3277 lm



Ausführung DALI ONETRAK | Version DALI ONETRAK

Code + **DDO (BWS-30NW11-1DDO)**



120 lm/W in Vorbereitung | 120 lm/W in preparation

Farben | Colors

☐ Weiß | White
 ☒ Schwarz | Black
 ☐ Schwarz/Weiß | Black/White
 ☐ Alugrau | Aluminium