

BWS 40



- LED Schienenstrahler
- Gehäuse aus lackiertem Alu-Druckguss, klares Schutzglas
- COB-LED-Modul in 4 Ausstrahlwinkeln 15°/24°/40°/60°
- Eutrac®-3-Phasen-Adapter
- 4 Standard Gehäusefarbkombinationen (andere Farbkombinationen auf Anfrage)
- Schutzart: IP20
- Schutzklasse: I
- Integriertes elektronisches Versorgungsteil (Standard: 30.000h / 50.000h auf Anfrage)
- CRI >90

Auf Anfrage

- Dimmbare Version
- Anbaumontage mit Deckenrosette
- Einhängestrahler für Rasterdecken
- Für Lebensmittel (Gemüse-, Back- und Fleischwaren) optimierte Versionen

- LED power-track-light
- Body in coated die-cast aluminium, clear glass
- COB-LED-module with optics in 15°/24°/40°/60°
- Eutrac®-3-phase-adapter
- 4 standard housing colours combination (other colour combinations on request)
- Protection Rating: IP20
- Protection Class: I
- Built in electronic power supply (standard 30.000h / 50.000h on request)
- CRI >90

On request

- Dimmable version
- Surface mounted with ceiling rose
- Spotlight to hang in grid ceilings
- Optimized versions for groceries (vegetables, bakery and meat products)

Stromschienen | Power-tracks

Siehe ab Seite 50 | See from page 50





Ab/From
01/2024
120lm/W



BWS-40 | 220-240 V | LED | CRI 90




Beam Angle	Color Temperature	Model 1	Model 2	Model 3	Model 4	Power
15°						39 W
4000 K		BWS-40NW11-1S	BWS-40NW12S	BWS-40NW12-1S	BWS-40NW17-7S	5182 lm
3500 K		BWS-40WNW11-1S	BWS-40WNW12S	BWS-40WNW12-1S	BWS-40WNW17-7S	5131 lm
3000 K		BWS-40WW11-1S	BWS-40WW12S	BWS-40WW12-1S	BWS-40WW17-7S	5081 lm
2700 K		BWS-40SW11-1S	BWS-40SW12S	BWS-40SW12-1S	BWS-40SW17-7S	4979 lm
24°						39 W
4000 K		BWS-40NW11-1	BWS-40NW12	BWS-40NW12-1	BWS-40NW17-7	5257 lm
3500 K		BWS-40WNW11-1	BWS-40WNW12	BWS-40WNW12-1	BWS-40WNW17-7	5205 lm
3000 K		BWS-40WW11-1	BWS-40WW12	BWS-40WW12-1	BWS-40WW17-7	5154 lm
2700 K		BWS-40SW11-1	BWS-40SW12	BWS-40SW12-1	BWS-40SW17-7	5050 lm
40°						39 W
4000 K		BWS-40NW11-1F	BWS-40NW12F	BWS-40NW12-1F	BWS-40NW17-7F	5347 lm
3500 K		BWS-40WNW11-1F	BWS-40WNW12F	BWS-40WNW12-1F	BWS-40WNW17-7F	5294 lm
3000 K		BWS-40WW11-1F	BWS-40WW12F	BWS-40WW12-1F	BWS-40WW17-7F	5242 lm
2700 K		BWS-40SW11-1F	BWS-40SW12F	BWS-40SW12-1F	BWS-40SW17-7F	5137 lm
60°						39 W
4000 K		BWS-40NW11-1-60	BWS-40NW12-60	BWS-40NW12-1-60	BWS-40NW17-7-60	5217 lm
3500 K		BWS-40WNW11-1-60	BWS-40WNW12-60	BWS-40WNW12-1-60	BWS-40WNW17-7-60	5166 lm
3000 K		BWS-40WW11-1-60	BWS-40WW12-60	BWS-40WW12-1-60	BWS-40WW17-7-60	5115 lm
2700 K		BWS-40SW11-1-60	BWS-40SW12-60	BWS-40SW12-1-60	BWS-40SW17-7-60	5013 lm



Ausführung DALI ONETRACK | Version DALI ONETRACK

Code + **DDO (BWS-40NW11-1DDO)**

120 lm/W in Vorbereitung | 120 lm/W in preparation



Farben | Colors

☐ Weiß | White
 ☒ Schwarz | Black
 ☐ Schwarz/Weiß | Black/White
 ☐ Alugrau | Aluminium