

DX/DXS



- LED Strahler für Wand- und Bodenmontage
- Gehäuse Aluminium
- Ø54 mm
- Mit Erdspeiß (L250 mm) für Bodenmontage 3 verschiedene Höhen: 70 mm; 170 mm und 510 mm
- Schwenkbar 220°
- Oberflächenbehandlung Aluminium und bronze eloxiert
- Gehärtetes, transparentes Glas
- Aluminium Wabenraster
- Schutzart: IP65
- Schutzklasse: II
- Direktanschluss an 230V (ohne externes Netzteil)
- Inklusive Zuleitung 500 mm

Auf Anfrage

- 2700 K
- Farbe schwarz

- LED projector for wall or ceiling installation
- Body made of aluminium
- Ø54 mm
- With earth spike (L250 mm) 3 different heights: 70 mm; 170 mm; 510 mm
- 220° swiveling
- Surface treatment aluminum and bronze anodized
- Tempered transparent glass
- Aluminium Honeycomb
- Protection Rating: IP65
- Protection Class: II
- Direct connection to 230V (without external power supply)
- Incl. 500 mm power supply cable


On request

- 2700 K
- Black color




DX
LED Wand- und Bodenaufbaustrahler
LED wall and floor mounted spotlight
220-240V / CRI >80


Beam Angle	Power	4000 K	3000 K
52°	6 W	● DX-54NW7 149 lm	● DX-54NW08 149 lm
		● DX-54WW7 142 lm	● DX-54WW08 142 lm
26°	6 W	● DX-54NW7S 277 lm	● DX-54NW08S 277 lm
		● DX-54WW7S 277 lm	● DX-54WW08S 277 lm




DXS
LED Strahler mit Erdspieß
LED spotlight with earth spike
ø54 / 220-240V / CRI >80



Beam Angle	Height	4000 K	3000 K
52°	H 70 mm	● DXS-54NW7	● DXS-54NW08
		● DXS-54WW7	● DXS-54WW08
26°		● DXS-54NW7S	● DXS-54NW08S
		● DXS-54WW7S	● DXS-54WW08S



Beam Angle	Height	4000 K	3000 K
52°	H 170 mm	● DXSM-54NW7	● DXSM-54NW08
		● DXSM-54WW7	● DXSM-54WW08
26°		● DXSM-54NW7S	● DXSM-54NW08S
		● DXSM-54WW7S	● DXSM-54WW08S



Beam Angle	Height	4000 K	3000 K
52°	H 510 mm	● DXSL-54NW7 149 lm	● DXSL-54NW08 149 lm
		● DXSL-54WW7 142 lm	● DXSL-54WW08 142 lm
26°		● DXSL-54NW7S 277 lm	● DXSL-54NW08S 277 lm
		● DXSL-54WW7S 264 lm	● DXSL-54WW08S 264 lm



● Alu eloxiert | Anodized Aluminium ● Bronze eloxiert | Anodized Bronze

