



Description

FLEXY LED-FLEX-MODUL, 5m, 1400 LED, 19,2W/M, 280LED's/M, 4000K, 24V DC, Ra 90, 1958lm/M (120°), IP20, useful luminous flux: 980 lm/0,5m (360°), energy consumption in on-mode: 10 kWh/1000h (9,6 W)/0,5 m, dimmable with specific drivers, L70B50: 36.000 h

General data

Degree of protection (IP):	IP20
Model:	Strip
Mounting method:	Surface mounting
Protection class:	III
Self-adhesive:	Yes

Photometric data



Beam angle:	120°
Colour of light:	White
Colour rendering index CRI:	90-100
Colour temperature:	4000K
Lamp power per meter:	19.2W
Luminaire efficacy:	102lm/W
Luminous flux per meter:	1958lm
Number of nodes per meter:	280

Electrical data

Exchangeable control gear:	Yes
Length of particular segments:	25mm
Lowest bending radius:	30mm
Voltage type:	DC

Product dimensions

Length:	5000mm
Width:	10mm



Address/Contact

A.L.S. Architektonische Lichtsysteme GmbH
 Mastorter Str. 31 | 88069 Tettnang (Germany)
 tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
 E-Mail: info@als.de | Web: www.als.de