



Description

FLEXY LED-FLEX-MODUL, 5m, 350 LED, 4,8W/M, 70LED's/M, 24V DC, 2700K, Ra 90, IP20, useful luminous flux: 220 lm/0,5m (360°), energy consumption in on-mode: 3 kWh/1000h (2,4 W)/0,5 m, dimmable with specific drivers, L70B50: 36.000 h

General data

Degree of protection (IP):	IP20
Model:	Strip
Mounting method:	Surface mounting
Protection class:	III
Self-adhesive:	Yes

Photometric data



Beam angle:	120°
Colour of light:	White
Colour rendering index CRI:	90-100
Colour temperature:	2700K
Lamp power per meter:	4.8W
Luminaire efficacy:	92lm/W
Luminous flux per meter:	442lm
Number of nodes per meter:	70

Electrical data

Exchangeable control gear:	Yes
Length of particular segments:	100mm
Lowest bending radius:	30mm
Voltage type:	DC

Product dimensions

Length:	5000mm
Width:	8mm



Address/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de