



FLEXY-700

9,6 W/M/24Vdc, L5000 mm | IP20 | CRI>90 | B 8 mm
140 LED/M, 100 Segmente = 700 LED
Kürzbar | Trimmable: 50 mm (7 LED)



4000 K	FLEXY-700NW	960 lm/m	
3000 K	FLEXY-700WW	902 lm/m	
2700 K	FLEXY-700SW	893 lm/m	



Rückseite mit 3M Klebeband | Backside with 3M adhesive tape

FLEXY1-350

14,4 W/M/24Vdc, L5000 mm | IP20 | CRI>90 | B 10 mm
70 LED/M, 50 Segmente = 350 LED
Kürzbar | Trimmable: 100 mm (7 LED)



4000 K	FLEXY1-350NW	1152 lm/m	
3000 K	FLEXY1-350WW	1080 lm/m	
2700 K	FLEXY1-350SW	1022 lm/m	



Rückseite mit 3M Klebeband | Backside with 3M adhesive tape

FLEXY8

14,4 W/M/24Vdc, L5000 mm | IP20 | CRI>90 | B 8 mm
400 LED/M, 250 Segmente = 2000 LED
Kürzbar | Trimmable: 20 mm (8 LED)



4000 K	FLEXY8-2000NWN	1296 lm/m	
3000 K	FLEXY8-2000WWN	1282 lm/m	



9,6 W/M/24Vdc

2700 K	FLEXY8-2000SWN	846 lm/m	
--------	-----------------------	----------	--

Rückseite mit 3M Klebeband | Backside with 3M adhesive tape

FLEXY2-800

19,2 W/M/24Vdc, L5000 mm | IP20 | CRI>90 | B 10 mm
160 LED/M, 100 Segmente = 800 LED
Kürzbar | Trimmable: 50 mm (8 LED)



4000 K	FLEXY2-800NW	2208 lm/m	
3000 K	FLEXY2-800WW	2112 lm/m	
2700 K	FLEXY2-800SW	2150 lm/m	



Rückseite mit 3M Klebeband | Backside with 3M adhesive tape

FLEXY-1400

19,2 W/M/24Vdc, L5000 mm | IP20 | CRI>90 | B 10 mm
280 LED/M, 200 Segmente = 1400 LED
Kürzbar | Trimmable: 25 mm (7 LED)



4000 K	FLEXY-1400NW	1958 lm/m	
3000 K	FLEXY-1400WW	1862 lm/m	
2700 K	FLEXY-1400SW	1843 lm/m	



Rückseite mit 3M Klebeband | Backside with 3M adhesive tape

FLEXY-350

4,8 W/M/24Vdc, L5000 mm | IP20 | CRI>90 | B 8 mm
70 LED/M, 50 Segmente = 350 LED
Kürzbar | Trimmable: 100 mm (7 LED)



4000 K	FLEXY-350NW	480 lm/m	
3000 K	FLEXY-350WW	451 lm/m	
2700 K	FLEXY-350SW	442 lm/m	



Rückseite mit 3M Klebeband | Backside with 3M adhesive tape

Zubehör | Accessories



Einspeiser
End Feed
2 Pin, IP20

Längsverbinder
Straight coupler
2 Pin, IP20



Einspeiser
Feeder
2 Pin, IP20

Längsverbinder
Straight coupler
2 Pin, IP20



T/Winkel-Verbinder flexibel
T-connector flexible
2-polig | 2 pole, IP20

Für Flexy Breite 8mm	Z-FL8ES L15,6xB/W9,7xH5,3 mm	Z-FL8LS L15,6 x B/W9,7 x H5,3 mm	Z-FL8E L28xB/W12,7xH8 mm	Z-FL8L L28xB/W12,7xH8 mm	Z-FL8TWV
Für Flexy Breite 10mm	Z-FL10ES L21,7xB/W11,7xH5,3 mm	Z-FL10LS L21,7xB/W11,7xH5,3 mm	Z-FL10E L24xB/W14,6xH8 mm	Z-FL10L L24xB/W14,6xH8 mm	Z-FL10TWV

Die Verbinder können nur einmal geschlossen werden.
Aufgrund der flachen Bauweise für Profile geeignet.
The connectors can be closed only once.
Suitable for profiles with flat design.

Die Verbinder können wieder geöffnet werden.
The connectors can be re-opened.

Kürzbar | Trimmable



Linearverbinder | Connector linear
Z-FLLV
2-polig | 2 pole, 0,5mm²
L26xB/W11xH8 mm



T-Verbinder | T-connector
Z-FLTLV
1-polig | 2 pole, 0,5mm²
L18,5xB/W15xH8 mm



Verteiler 2-fach | Distributor 2-way
Z-FLVERTEILER2
2-polig | 2 pole, 0,5mm², max 24V/6A, IP40
Inkl. 3 Steckverbinder | Incl. 3 plug connectors

