

Description

FLEXY, LED-FLEX-MODUL, 5m, 350 LED, Useful
luminous flux: 635 lm/0,5 m (360°), Energy
consumption in on-mode: 8 kWh/1000h (7,2 W)/0,5
m, 70LED's/M, 2700K, 24V DC, Ra 90, IP20,
dimmable with specific drivers, L70B50: 36.000 h

General data

Degree of protection (IP):	IP20
Model:	Strip
Mounting method:	Surface mounting
Protection class:	III
Self-adhesive:	Yes

Photometric data



Beam angle:	120°
Colour of light:	White
Colour rendering index CRI:	90-100
Colour temperature:	2700K
Lamp power per meter:	14.4W
Luminaire efficacy:	71lm/W
Luminous flux per meter:	1022lm
Number of nodes per meter:	70

Electrical data

Exchangeable control gear:	Yes
Length of particular segments:	100mm
Lowest bending radius:	30mm
Voltage type:	DC

Product dimensions

Length:	5000mm
Width:	10mm



Address/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de