





Description

FLEXY, LED-FLEX-MODUL, 5m, 800 LED's, 19,2 W/m, 160 LED's/M, 2700K, 24V, Ra 90, IP20, useful luminous flux: 1040 lm/0,5m (360°), energy consumption in on-mode: 10 kWh/1000h (9,6 W)/0,5 m, dimmable with specific drivers, L70B50: 36.000 h

General data

Degree of protection (IP):	IP20
Model:	Strip
Mounting method:	Surface mounting
Protection class:	III
Self-adhesive:	Yes

Photometric data

Beam angle:	120°
Colour of light:	White
Colour rendering index CRI:	90-100
Colour temperature:	2700K
Lamp power per meter:	19.2W
Luminaire efficacy:	110lm/W
Luminous flux per meter:	2112lm
Number of nodes per meter:	160

Electrical data

Exchangeable control gear:	Yes
Length of particular segments:	50mm
Lowest bending radius:	30mm
Voltage type:	DC

Product dimensions

Length:	5000mm
Width:	10mm



Address/Contact

A.L.S. Architektonische Lichtsysteme GmbH
 Mastorter Str. 31 | 88069 Tettnang (Germany)
 tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
 E-Mail: info@als.de | Web: www.als.de