



## Description


FLEXY, LED-FLEX-MODUL, 5m, 1600 LED's, 10 W/m, 320 LED's/M, 4000K, 24V, Ra 90, IP20, useful luminous flux: 518 lm/0,5m (360°), energy consumption in on-mode: 5 kWh/1000h (5 W)/0,5 m, dimmable with specific drivers, L70B50: 33.000 h

## General data

|                                   |                  |
|-----------------------------------|------------------|
| <b>Degree of protection (IP):</b> | IP20             |
| <b>Model:</b>                     | Strip            |
| <b>Mounting method:</b>           | Surface mounting |
| <b>Protection class:</b>          | III              |
| <b>Self-adhesive:</b>             | Yes              |

## Photometric data

|                                    |        |
|------------------------------------|--------|
| <b>Beam angle:</b>                 | 120°   |
| <b>Colour of light:</b>            | White  |
| <b>Colour rendering index CRI:</b> | 90-100 |
| <b>Colour temperature:</b>         | 4000K  |
| <b>Lamp power per meter:</b>       | 10W    |
| <b>Luminaire efficacy:</b>         | 67lm/W |
| <b>Luminous flux per meter:</b>    | 990lm  |
| <b>Number of nodes per meter:</b>  | 320    |



Height: 2 mm

## Electrical data

|                                       |      |
|---------------------------------------|------|
| <b>Exchangeable control gear:</b>     | Yes  |
| <b>Lamp voltage:</b>                  | 0V   |
| <b>Length of particular segments:</b> | 50mm |
| <b>Voltage type:</b>                  | DC   |

## Product dimensions

|                      |        |
|----------------------|--------|
| <b>Height/depth:</b> | 2mm    |
| <b>Length:</b>       | 5000mm |
| <b>Width:</b>        | 8mm    |



## Address/Contact

A.L.S. Architektonische Lichtsysteme GmbH  
Mastorter Str. 31 | 88069 Tettnang (Germany)  
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30  
E-Mail: info@als.de | Web: www.als.de