





Description

HIGHWAY, pendant light fixture, LED, 33W, 3000K, incl. EVG and pendant set, opal cover made of PMMA, body color anodized aluminium

General data

Colour housing:	Aluminium
Degree of protection (IP):	IP20
Lamp holder:	None
Material cover:	Plastic, opal
Material housing:	Aluminium
Protection class:	I
With suspension:	Yes

Photometric data

Colour consistency (McAdam ellipse):	SDCM3
Colour of light:	White
Colour rendering index CRI:	80-89
Colour temperature:	3000K
Light outlet:	Direct/indirect
Light sharing:	Symmetric
Luminaire efficacy:	86lm/W
Max. system power:	31W
Rated luminous flux according to IEC 62722-2-1:	2654lm
Suitable for number of lamps:	4
Type of grid:	None
Unified Glare Ratio (UGR):	24.60

Electrical data

Exchangeable control gear:	Yes
No dim function:	Yes
Nominal voltage:	220V - 240V



Address/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de

Pendant luminaire

HAP-33WW70



Voltage type:

AC

With control gear:

Yes

Product dimensions

Height/depth:

90mm

Length:



1195mm

Pendant length:

1500mm

Width:

70mm



Misprints and errors excepted. Drawings and pictures are sketches. Dimensions and technical data are approximate. Length specifications without unit in millimeters. The Object photos shown are examples of applications independent of the actual effect. We reserve the right to make changes to the range, technology and design (without prior notice). Color deviations are due to printing technology, possible.

Adress/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de