

Description

1045GR4K LED 14W, 30°, 4000K, aluminium die cast housing, CRI 80, IK08, IP65, built in driver, anthracite

General data

Colour housing:	Anthracite
Degree of protection (IP):	IP65
Material housing:	Aluminium
Protection class:	II
Suitable for surface mounting:	Yes
Suitable for wall mounting:	Yes

Photometric data

Beam angle:	Medium beam 21-40°
Colour of light:	White
Colour rendering index CRI:	80-89
Colour temperature:	4000K
Light outlet:	Direct
Light sharing:	Symmetric
Luminaire efficacy:	8lm/W
Max. system power:	14W
Rated luminous flux according to IEC 62722-2-1:	144lm
Suitable for number of lamps:	4


Electrical data

Exchangeable control gear:	Yes
Impact strength:	IK08
No dim function:	Yes
Nominal voltage:	230V
Voltage type:	AC





Address/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de



Product dimensions

Height/depth:	102mm
Length:	100mm
Width:	100mm



Adress/Contact