





Description

MIN, Spotlight for contact tracks, CoB LED, 17W, 4000K COB, CRI >90, with 3-phase-electronic adapter, incl. power supply integrated in adapter, 36° beam angle, clear tempered glass, body white

General data

Adjustability:	Rotating and swivelling
Colour housing:	White
Degree of protection (IP):	IP20
Lamp holder:	None
Material housing:	Aluminium
Protection class:	II
Suitable for light-track mounting:	Yes

Photometric data

Beam angle:	Medium beam 21-40°
Colour consistency (McAdam ellipse):	SDCM3
Colour of light:	White
Colour rendering index CRI:	90-100
Colour temperature:	4000K
Light outlet:	Direct
Light sharing:	Symmetric
Luminaire efficacy:	140lm/W
Luminous flux:	2390lm
Max. system power:	17W
Rated luminous flux according to IEC 62722-2-1:	2390lm
Suitable for number of lamps:	1

Electrical data

Connection type:	Busbar adapter
Exchangeable control gear:	Yes



Address/Contact




A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de



No dim function:	Yes
Nominal voltage:	220V - 240V
Voltage type:	AC
With control gear:	Yes

Product dimensions

Height/depth:	164mm
Length:	255mm
Outer diameter:	90mm
Width:	95mm



Adress/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de