





Description

PEP LED light channel, with opal cover, DC48V, 11W, DC350mA, 31V, beam angle 110°, 2700K, warm white, CRI<80, black

General data

Adjustability:	Not adjustable
Colour housing:	Black
Degree of protection (IP):	IP20
Lamp holder:	None
Material housing:	Aluminium
Protection class:	III
Suitable for light-track mounting:	Yes
Surface protection:	Lacquered

Photometric data

Beam angle:	Extreme wide beam >80°
Colour of light:	White
Colour rendering index CRI:	80-89
Colour temperature:	2700K
Light outlet:	Direct
Light sharing:	Symmetric
Luminaire efficacy:	64lm/W
Luminous flux:	784lm
Max. system power:	11W
Rated luminous flux according to IEC 62722-2-1:	705lm
Suitable for number of lamps:	1

Electrical data

Connection type:	Busbar adapter
Exchangeable control gear:	Yes
No dim function:	Yes
Nominal voltage:	48V



Address/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de





Voltage type: DC

Product dimensions

Height/depth: 48mm

Length: 408mm

Width: 24.5mm



Adress/Contact

A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de