





Description

SLC, track spotlight, CoB LED, 1x26W, 3500K, with 3-phase adapter, including power supply, rotatable, 15° reflector, clear protective glass, white body

General data

Adjustability:	Rotating and swivelling
Colour housing:	White
Degree of protection (IP):	IP20
Lamp holder:	None
Material housing:	Aluminium
Protection class:	II
Suitable for light-track mounting:	Yes
Surface protection:	Lacquered

Photometric data

Beam angle:	Narrow beam 11 - 20°
Colour consistency (McAdam ellipse):	SDCM3
Colour of light:	White
Colour rendering index CRI:	90-100
Colour temperature:	3500K
Light outlet:	Direct
Light sharing:	Symmetric
Luminaire efficacy:	89lm/W
Luminous flux:	2305lm
Max. system power:	26W
Rated luminous flux according to IEC 62722-2-1:	2305lm
Suitable for number of lamps:	1

Electrical data

Connection type:	Busbar adapter
Exchangeable control gear:	Yes



Address/Contact



A.L.S. Architektonische Lichtsysteme GmbH
Mastorter Str. 31 | 88069 Tettnang (Germany)
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30
E-Mail: info@als.de | Web: www.als.de



No dim function:	Yes
Nominal voltage:	220V - 240V
Voltage type:	AC
With control gear:	Yes

Product dimensions

Height/depth:	228mm
Length:	110mm
Outer diameter:	84mm
Width:	84mm



Adress/Contact