





## Description

SLC, track spotlight, CoB LED, 1x26W, 3000K, with 3-phase adapter, including power supply, rotatable, 36° reflector, clear protective glass, white body

## General data

|                                           |                         |
|-------------------------------------------|-------------------------|
| <b>Adjustability:</b>                     | Rotating and swivelling |
| <b>Colour housing:</b>                    | White                   |
| <b>Degree of protection (IP):</b>         | IP20                    |
| <b>Lamp holder:</b>                       | None                    |
| <b>Material housing:</b>                  | Aluminium               |
| <b>Protection class:</b>                  | II                      |
| <b>Suitable for light-track mounting:</b> | Yes                     |
| <b>Surface protection:</b>                | Lacquered               |

## Photometric data

|                                                        |                    |
|--------------------------------------------------------|--------------------|
| <b>Beam angle:</b>                                     | Medium beam 21-40° |
| <b>Colour consistency (McAdam ellipse):</b>            | SDCM3              |
| <b>Colour of light:</b>                                | White              |
| <b>Colour rendering index CRI:</b>                     | 90-100             |
| <b>Colour temperature:</b>                             | 3000K              |
| <b>Light outlet:</b>                                   | Direct             |
| <b>Light sharing:</b>                                  | Symmetric          |
| <b>Luminaire efficacy:</b>                             | 92lm/W             |
| <b>Luminous flux:</b>                                  | 2382lm             |
| <b>Max. system power:</b>                              | 26W                |
| <b>Rated luminous flux according to IEC 62722-2-1:</b> | 2382lm             |
| <b>Suitable for number of lamps:</b>                   | 1                  |

## Electrical data

|                                   |                |
|-----------------------------------|----------------|
| <b>Connection type:</b>           | Busbar adapter |
| <b>Exchangeable control gear:</b> | Yes            |



## Address/Contact



A.L.S. Architektonische Lichtsysteme GmbH  
Mastorter Str. 31 | 88069 Tettnang (Germany)  
tel.: +49 7542 9344-0 | Fax: +49 7542 9344-30  
E-Mail: info@als.de | Web: www.als.de



|                           |             |
|---------------------------|-------------|
| <b>No dim function:</b>   | Yes         |
| <b>Nominal voltage:</b>   | 220V - 240V |
| <b>Voltage type:</b>      | AC          |
| <b>With control gear:</b> | Yes         |

**Product dimensions**

|                        |       |
|------------------------|-------|
| <b>Height/depth:</b>   | 228mm |
| <b>Length:</b>         | 110mm |
| <b>Outer diameter:</b> | 84mm  |
| <b>Width:</b>          | 84mm  |



**Adress/Contact**