





Description

UAL, Pendant-/Ceiling luminaire round, LED , 55W, color changeable 3000K/4000K, 220-240AC, CRI80, 120°, Ø800mm, height 86mm, incl. DALI power supply, opal PMMA diffuser, IP40, white



General data

Colour housing:	White
Degree of protection (IP):	IP40
Lamp holder:	None
Material cover:	Plastic, opal
Material housing:	Aluminium
Protection class:	I
Suitable for ceiling mounting:	Yes
Suitable for surface mounting:	Yes
Suitable for wall mounting:	Yes
Surface protection housing:	Powder coating

Photometric data

Beam angle:	Extreme wide beam >80°
Colour consistency (McAdam ellipse):	SDCM3
Colour of light:	White
Colour rendering index CRI:	80-89
Colour temperature:	3000K - 4000K
Colour temperature adjustable:	Positions
Light distributor:	None
Light outlet:	Direct/indirect
Light sharing:	Symmetric
Luminaire efficacy:	120lm/W
Max. system power:	55W
Rated luminous flux according to IEC 62722-2-1:	6589lm

Address/Contact



Suitable for number of lamps:

5

Type of grid:

None

Unified Glare Ratio (UGR):

20.50

Electrical data

Dimming DALI:

Yes

Exchangeable control gear:

Yes

No dim function:

Yes

Nominal current:

500mA

Nominal voltage:

220V - 240V

Type of control gear:

LED operating device
current-controlled

Voltage type:

AC

With control gear:

Yes

Product dimensions

Height/depth:

86mm

Outer diameter:

800mm

Address/Contact